




| REVISIONS | | |
|-----------|-----------|-------------|
| REV | DATE | DESCRIPTION |
| A | 3/22/2012 | |

| PARTS LIST | | | |
|------------|------|----------|-------------|
| ITEM | QUAN | PART NUM | DESCRIPTION |
| | | | |


- 1 ----> 1 (RED/WHT WIRE = POWER +5VDC)
- 2 ----> 2 (GREEN/WHT WIRE = BEEPTTL)
- 3 ----> 3 (WHITE = ANALOG SIGNAL)
- 4 ----> 4 (BLACK/WHT = GROUND)
- 5 ----> 5 (ORG/WHT = PLAY VCHIP)
- 6 ----> 6 (BLU/WHT = BEEP PITCH CHANGE)
- 7 ----> 7 (YEL/WHT = VCHIP FWD)
- 8 ----> 8 (VIO/WHT = SPARE I/O)
- 9 ----> N/C
- 10 ----> N/C

10 POSITION FEMALE HIROSE
CONNECTOR P/N: HR10A-10P-10S(73)
REAR VIEW OF CONNECTOR
OR SOLDER VIEW

10 POSITION FEMALE HIROSE
CONNECTOR P/N: HR10A-10P-10S(73)
REAR VIEW OF CONNECTOR
OR SOLDER VIEW



THIS DRAWING IS THE PROPERTY OF DEPOTSTAR INC., AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS WITHOUT PERMISSION.

| | | |
|------------------------------|--------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| MATERIAL | TOLERANCE METRIC .X= .XX=.010 .XX= .XXX=.005 ANGLE DIM. + - 1/2 |  RAMSEY MINNESOTA |
| FINISH | MODEL NO. 000 | |
| REF. DRAWINGS WHERE USED: | ECO NUMBER 000 | TITLE AOA I/F Module to AOA Dual I/F Module Cable |
| | DRAWN BY XP | DATE 03/22/12 |
| NO. REQD PER UNIT | CHECKED | SCALE N/A |
| | SIZE A | DRAWING NO. AOA-4029EXTDUAL |
| | | REV. A |